

Printer Model		DS-2200T			Data Transfer	TCP/IP network interface /USB
Printhead		Epson i3200-A1 (8H 4C/8C)			OS Required	Windows7/10 64 bits (Flagship/Professional Version)
Printing Speed	High Resolution Mode	4pass	65㎡/h	30㎡/h	Computer Require	Hard disk: SATA500/Hard disk format: NTFS/CPU: Inter i5/RAM: 8G-16G
	Production Mode	3pass	85㎡/h	40㎡/h	Drying System	Synchronous drying before and after printing, the temperature can be adjusted according to different fabrics.
	Sketch Mode	2pass	105㎡/h	50㎡/h	Ink Purge Control System	ink scraping and moisturizing system by patent
Ink	Type	Reactive ink , Acidic ink, Disperse direct printing ink			Media Type	Textile fabrics of animal and plant proteins, Chemical fiber, Banner cloth, light box cloth etc
	Color	M / Y / C / K / LM / LC (O, B optional,FM,FY)			Maximum Power	7KW (Including heating system power5KW)
Media Max Diameter		350mm			Operation Environment	Humidity: 40%-70% Temperature:20-30℃
Printing Width		2150mm			Power Supply	AC220V±10% 50HZ
Printing Thickness		≤3mm			N.W	1800kg
RIP Software		Maincenter/PrintFactory/Neostampa			Printer Size	L*W*H: 4155*1530*2021mm
Image Format		TIFF / JPG / EPS / PDF			Package Size	L*W*H: 4165*1540*2031mm