

Technical Parameters:

Model		HT1800UV-GEN6
Printing Information		
Printhead		GEN6
Number of Printheads		2 - 8 pcs (3-row)
Resolution		605*1800 DPI
Productivity	Draft Mode	65 m ² /h
	Production Mode	56 m ² /h
	Quality Mode	41 m ² /h
Printing Modes		Unidirectional & Bidirectional
Media & Ink		
Max. Print Width		1800 mm
Max. Media Thickness		50 mm
Media		Flexible flat materials
Ink Type		UV (VOC free)
Ink Colors		CMYK, Lc, Lm, W
Features		
Curing		Water-cooled UV_LED Lamp
Transfer		USB
RIP Support		Caldera / Onyx (Optional Purchase)
Input		PDF, JPEG, TIFF, EPS, AI.....
Dimensions & Weight		
Printer Dimensions		4515*960*1335 mm (L*W*H)
Net Weight		1200 KG
Gross Weight		1500 KG
Power & Environment		
Power Consumption		4 kW (19A)
Power Supply		220VAC 50Hz 3P/N/PE
Environmental Requirements	Independent, clean, low-dust, low-light workspace with good ventilation	
	Operating Temperature: 18°C ~ 30°C (64°F ~ 86°F)	
	Relative Humidity: 30% ~ 70% (non-condensing)	
Others		Requires ADP / Computer


Industrial Digital Inkjet Comprehensive Solution Provider



Independent printhead-drive technology



Self-developed control system



Self-developed MES system



Independent ink industrial chain



Remote service maintenance system and local services

Shenzhen HandTop Tech Co., Ltd.

www.hanglorygroup.com

Add:Baolong 3rd Road and Gaoke Avenue Intersection, Longgang District, Shenzhen, Guangdong

Tel:(+86)0755-2308 0896 Fax:(+86)0755-2321 7841 E-mail:info@hanglorygroup.com

©Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.



VI.0/2025