



*Illustration purpose

Technical Parameters:

Model		HTH2512UV
Printing Information		
Printhead		GEN6
Number of Printheads		2-8 pcs (3-Row)
Resolution		1200*1200 DPI
Productivity	Draft Mode	77 m²/h
	Production Mode	57 m²/h
	Quality Mode	40 m²/h
Printing Modes		Bi-directional high speed
Media & Ink		
Max. Print Width		2.5*1.2 m
Max. Media Thickness		100 mm
Media		Finished shoes, bags, toys, handicrafts, home decoration, carving paintings, etc.
Ink Type		Eco-friendly UV-curable ink (VOC-free)
Ink Colors		CMYK, Lc, Lm, V, W
Features		
Curing		LED curing (adjustable power)
Transfer		USB
RIP Support		Caldera / Onyx (Optional Purchase)
Input		PDF, JPEG, TIFF, EPS, AI.....
Dimensions & Weight		
Printer Dimensions		4670*2510*1380 mm (L*W*H)
Net Weight		1150 KG
Gross Weight		1745 KG
Power & Environment		
Power Consumption		8.3 kW (20A)
Power Supply		400VAC 50Hz 3L/N/PE
Environmental Requirements	Independent, clean, low-dust, low-light workspace with good ventilation	
	Operating Temperature: 18°C ~ 30°C (64°F ~ 86°F)	
	Relative Humidity: 30% ~ 70% (non-condensing)	
Others		Requires ADP / Computer


Industrial Digital Inkjet Comprehensive Solution Provider



Independent printhead-drive technology



Self-developed control system



Self-developed MES system



Independent ink industrial chain



Remote service maintenance system and local services

Shenzhen HandTop Tech Co., Ltd.

www.hanglorygroup.com

Add:Baolong 3rd Road and Gaoke Avenue Intersection, Longgang District, Shenzhen, Guangdong

Tel:(+86)0755-2308 0896

Fax:(+86)0755-2321 7841

E-mail:info@hanglorygroup.com

©Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.



V1.0/2025