

Technical Parameters:

Model		HTH3200UV-Turbo
Printing Information		
Printhead		Kyocera
Number of Printheads		4-12 pcs
Resolution		363*3600 DPI
Productivity	Draft Mode	156 m²/h
	Production Mode	115 m²/h
	Quality Mode	82 m²/h
Printing Modes		Unidirectional & Bidirectional
Media & Ink		
Max. Print Width		3200 mm
Max. Media Thickness		2 mm
Media		A wide variety of roll printing materials in terms of soft film、coated banner, car wrapping, flex banner etc.
Ink Type		Eco-friendly UV-curable ink (VOC-free)
Ink Colors		CMYK、Lc、Lm、W
Features		
Curing		LED Curing (adjustable power)
Transfer		USB
RIP Support		Caldera / Onyx (Optional Purchase)
Input		PDF, JPEG, TIFF, EPS, AI.....
Dimensions & Weight		
Printer Dimensions		5985 * 1850 * 1900 mm (L*W*H)
Net Weight		2800 KG
Gross Weight		3600 KG
Power & Environment		
Power Consumption		8.7 kW (38A)
Power Supply		230VAC 50Hz P/N/PE
Environmental Requirements	Independent, clean, low-dust, low-light workspace with good ventilation	
	Operating Temperature: 18°C ~ 30°C (64°F ~ 86°F)	
	Relative Humidity: 30% ~ 70% (non-condensing)	
Others		Requires ADP / Computer


Industrial Digital Inkjet Comprehensive Solution Provider



Independent printhead-drive technology



Self-developed control system



Self-developed MES system



Independent ink industrial chain



Remote service maintenance system and local services

Shenzhen HandTop Tech Co., Ltd.

www.hanglorygroup.com

Add:Baolong 3rd Road and Gaoke Avenue Intersection, Longgang District, Shenzhen, Guangdong

Tel:(+86)0755-2308 0896

Fax:(+86)0755-2321 7841

E-mail:info@hanglorygroup.com

©Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.



VI.0/2025