

Printer Model		NEO N-6800UV						
Printhead		KM1024(12-36H YMCK LC LM)						
Printing Speed	Sketch mode	4pass	One group	40mf/h	two groups	80mf/h	Three groups	120 mf/h
	Production Mode	6pass		30mf/h		60mf/h		90mf/h
	High Resolution Mode	8pass		20mf/h		40mf/h		60mf/h
Printhead		KM1024(8-24H YMCK)						
Printing Speed	Sketch mode	4pass	One group	40mf/h	two groups	80mf/h	Three groups	120 mf/h
	Production Mode	6pass		30mf/h		60mf/h		90mf/h
	High Resolution Mode	8pass		20mf/h		40mf/h		60mf/h
Ink	Type	Imported environment-friendly UV ink (Soft/Neutral)						
	Color	M /Y /C /K /LM /LC						
Media Max Diameter		350mm						
Printing width		6800mm						
Printing Thickness		≤2mm						
RIP Software		PHOTO PRINT						
Image Format		TIFF /JPG /EPS /PDF						
Data Transfer		TCP /IP network interface /USB						
Drying		LED-UV lamp curing						
Moisture control		Patented automatic ink pressing moisturizing cleaning system						
Media Type		All UV flex banner, coated banner, reflective transfer film, back interlining cloth, PE light box panel						
Maximum Power		10KW (Including cooling system power 2KW)						
Operation Environment		Humidity: 40%-70% Temperature: 20-30℃						
Power Supply		AC220V±10% 50HZ						
Operation Air Pressure		0.6MPA						
N.W		17800kg						
Printer Size		L*W*H: 10670*2558*3328mm						
Separate Packing		L*W*H: 10670*2000*2558mm						
OS Required		Windows7/10 64 bits (Flagship/Professional Version)						
Computer Required		Hard disk: SATA500/Hard disk format: NTFS/CPU: Inter i5/RAM: 8G-16G						